



## Nondestructive Testing

The most common method for nondestructive material testing is ultrasonic testing, especially ultrasonic weld seam testing. This standard ultrasound inspection detects invisible cracks, inclusions, cavities and discontinuities quickly and reliably.

Ultrasonic wall thickness measurement as part of non-destructive testing is one of the most common methods of ultrasonic technologies. In addition to the classic measurement of wall thickness as part of quality control, our precise wall thickness measurement devices can also be used to detect failures caused by erosion and corrosion on ships, storage tanks, pipelines as well as machines and components.



**Flaw Detection**  
**SONOSCREEN ST10**



**Wall Thickness Measurement**  
**SONOWALL Series**



## Air-coupled Ultrasonic Inspections SONOAIR

DO YOU HAVE ANY QUESTIONS?

---



Then contact us!

Devin Mooneyhan

+1 (631)629 - 2463

[dmooneyhan@sonotecusa.com](mailto:dmooneyhan@sonotecusa.com)

### NEWS:

---

18.12.2018

**SONOTEC end-of-the-year review: strengthen international networks - foster innovations - invest in the future**

[more News...](#)

### EVENT CALENDAR:

---

01.04.2019

**ASNT Research Symposium 2019**

[all Events...](#)

### CUSTOMER REVIEWS:

---

**[Our customers on our NDT products](#)**

[all customer reviews...](#)