



Wall Thickness Measurement

Wall thickness measurement as part of non-destructive testing is one of the most common uses of ultrasonic technologies. In addition to the classic measurement of wall thickness as part of quality control, our precise wall thickness measurement devices can also be used to detect damage caused by erosion and corrosion on, for example, ships, storage tanks, pipelines and cranes. We have a variety of versions of our devices for all types of applications.

Detailed Product Information



SONOWALL 70

New A-scan / B-scan thickness gage



SONOWALL 50

with integrated data logger for precise wall thickness measurement



SONOWALL 60

for wall thickness measurement of corroded surfaces and surfaces with protective coatings



SONOSCAN Dual-Element Probes

Dual Element Probes with two separated elements



SONOSCAN Straight Beam Probes

Robust Pulse-Echo Probes

DO YOU HAVE ANY QUESTIONS?



Then contact us!

Devin Mooneyhan

+1 (631)629 - 2463

dmooneyhan@sonotecusa.com

NEWS:

18.12.2018

SONOTEC end-of-the-year review: strengthen international networks - foster innovations - invest in the future

[more News...](#)

| EVENT CALENDAR:

01.04.2019

ASNT Research Symposium 2019

[all Events...](#)

CUSTOMER REVIEWS:

[Our customers on our NDT products](#)

[all customer reviews...](#)